
Flash Magic - NON PRODUCTION USE ONLY
File ISP Options Tools Help
Step 1 - Communications
Select Device...
LPC2368 Ethernet
IP Address:
192.168.0.111
MAC Address:
0c-1d-12-e0-1f-10
See the Ethernet Bootloader chapter in the manual for details
Step 2 - Erase
Erase block 12 (0x028000-0x02FFFF)
Erase block 13 (0x030000-0x037FFF)
Erase block 14 (0x038000-0x03FFFF)
Erase block 15 (0x040000-0x047FFF)
Erase block 16 (0x048000-0x04FFFF)
Erase block 17 (0x050000-0x057FFF)
Erase all Flash+Code Rd Prot
Erase blocks used by Hex File
Step 3 - Hex File
Hex File:
AP\EthernetBootloader\User Code Sample Blinky\Flash\Blinky.hex
Browse...
Modified: Wednesday, March 3, 2010, 5:52:53 PM
more info
Step 4 - Options
Verify after programming
Fill unused Flash
Gen block checksums
Execute
Step 5 - Start!
Start
On-Line training classes for microcontrollers and embedded networking and Internetworking
www.esacademy.com/faq/classes
0


Flash Magic
Failed to find an ethernet interface.
OK


C:\WINDOWS\system32\cmd.exe
Windows IP Configuration
Ethernet adapter Local Area Connection:
Media State . . . . . : Media disconnected
Ethernet adapter Wireless Network Connection:
Connection-specific DNS Suffix . :
IP Address. . . . . : 192.168.0.11
Subnet Mask . . . . . : 255.255.255.0
Default Gateway . . . . . : 192.168.0.1
Ethernet adapter Local Area Connection 2:
Media State . . . . . : Media disconnected