

```
C:\WINDOWS\system32\cmd.exe

Windows IP Configuration

Ethernet adapter Local Area Connection 2:

    Media State . . . . . : Media disconnected
Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address . . . . . : 192.168.0.12
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.0.1
```

DHCP Client Lease Info			
	MAC Address	IP Address	Expires
<input type="radio"/>	001b77d75e05	192.168.0.10	Mar 10 11:33:07
<input type="radio"/>	00248c5f54a8	192.168.0.12	Mar 10 11:33:44
<input type="radio"/>	009100006115	192.168.0.18	Mar 10 11:37:45
<input type="radio"/>	0001e64f1a32	192.168.0.41	*** STATIC IP ADDRESS **
Current System Time: Wed Mar 10 10:37:52 2010			

Flash Magic - NON PRODUCTION USE ONLY

FileISPOptionsToolsHelp

Step 1 - Communications

Select Device...LPC2368 Ethernet

IP Address:192.168.0.111

MAC Address:0c-1d-12-e0-1f-10

See the Ethernet Bootloader chapter in the manual for details

Step 2 - Erase

Erase block 2 (0x002000-0x002FFF)
Erase block 3 (0x003000-0x003FFF)
Erase block 4 (0x004000-0x004FFF)
Erase block 5 (0x005000-0x005FFF)
Erase block 6 (0x006000-0x006FFF)
Erase block 7 (0x007000-0x007FFF)

☒ Erase all Flash+Code Rd Prot
☐ Erase blocks used by Hex File

Step 3 - Hex File

Hex File:C:\Projects\test uVision\Ethernet IAP\EthernetBootloader\User Co

Browse...

Modified: Wednesday, March 10, 2010, 11:42:11 AM

more info

Step 4 - Options

☒ Verify after programming
☒ Fill unused Flash
☐ Gen block checksums
☐ Execute

Step 5 - Start!


Start

Rotating, fully customizable, remotely updated Internet links. Embed them in your application!

www.embeddedhints.com

0

Flash Magic



Failed to find an ethernet interface.

OK